

CENOVNIK D-LINK MREŽNE OPREME

Važi od 20. Januara 2021.

MODEL		ŠIFRA	OPIS	Cena sa PDV	CENA
SWITCHEVI					
GO-SW-8E		R0668	10/100Mbps Megabitni 8-portni switch; Dimenzije: 130 x 79.2 x 22.8 mm.	11,32	9,43
GO-SW-5G		R0837	10/100/1000Mbps 5-portni Gigabitni switch; Dimenzije: 97 x 79 x 28 mm.	18,98	15,82
GO-SW-8G		R0839	10/100/1000Mbps 8-portni Gigabitni switch; Dimenzije: 128 x 68.5 x 25.4 mm.	25,96	21,63
NEUPRAVLJIVI (Unmanaged) SWITCHEVI					
DES-1016D		R1387	16 Portova Megabitni Switch; 16x 100 Mbps ports; Kontrola: Unmanaged, Standardi : IEEE 802.3, IEEE 802.3u, IEEE 802.3x; Dimenzije: 280 x 125.8 x 44 mm.	39,62	33,02
DES-1024D		R1388	24 Portova Megabitni Switch; 24x 100 Mbps Ports; Standardi: IEEE 802.1p, IEEE 802.3, IEEE 802.3u, IEEE 802.3x; Dimenzije: 280 x 125.8 x 44 mm.	53,72	44,77
DGS-1016D		R0642	16 portova Gigabitni SOHO switch; 16x 10/100/1000 Mbps Gigabit ports; Switching Fabric: 32 Gbps; IEEE 802.3x Flow Control; Podržava IEEE 802.1p QoS; Plug-and-play instalacija; Dimenzije: 280 x 180 x 44 mm.	92,54	77,12
DGS-1024D		R0538	24 Portova Gigabitni Switch; 24x 1000 Mbps ports; Standardi: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, Plug and Play Instalacija; Dimenzije: 280 x 180 x 44 mm.	125,06	104,22
NEUPRAVLJIVI (Unmanaged) POE SWITCHEVI					
DES-1005P		R0652	5 Porta Megabitni PoE switch; 5x 10/100 Mbps Fast Ethernet ports; 1x PoE port; Standardi: IEEE 802.1p, IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x; Switching Capacity: 1 Gbps; PoE Power Budget Max. 15.4 W; Dimenzije: 140 x 85 x 28 mm; Desktop	51,76	43,13
DGS-1008P		R1389	8 Porta Gigabitni PoE switch; 8x 10/100/1000 Mbps Gigabit ports; 4x PoE ports; Standardi: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x; Switching Capacity: 16 Gbps; PoE Power Budget Max. 52 W; Dimenzije: 190 x 120 x 38 mm; Desktop.	88,49	73,74
DES-1018P		R1390	16 Porta Megabitni PoE Switch; 2x Combo 1000Base-T/SFP ports; 16x PoE ports; PoE Power Budget Max. 246W; Dimenzije: 280 x 210 x 44 mm; Desktop / Rackmount.	328,58	273,82
UPRAVLJIVI (Managed) PoE SWITCHEVI					
DES-1210-28P		R1393	24 Porta Megabitni Smart PoE Switch; 24x 10/100BASE-TX ports; 2x 10/100/1000BASE-T ports; 2x Combo 1000Base-T/SFP ports; 24x PoE ports; Switching Capacity: 12.8 Gbps; PoE Power Budget Max. 193W; Dimenzije: 440 x 250 x 44 mm; Desktop / Rackmount.	324,06	270,05
DGS-3120-24SC-SI		R1458	24 Gigabit xStack L2+ Managed Gigabit Switches; 16 SFP Ports; 8 Combo 10/100/1000Base-T/SFP Ports; Switching Capacity: 88 Gbps; SD card slot; Dimenzije: 440 x 210 x 44 mm; Desktop / Rackmount.	869,94	724,95
DGS-1210-48		R1460	48-portni Gigabitni Switch; 44 10/100/1000 Mbps, 4 combo 10/100/1000BASE-T/SFP; Layer 2; Switching Capacity: 104 Gbps; Dimenzije: 440 x 210 x 44 mm; 19" standard rack mounting width, 1U.	425,34	354,45

MODEL		ŠIFRA	OPIS	Cena sa PDV	CENA
DPS-500A		R1461	Redudantno napajanje; Izlazna snaga: 140 W; Ulazni Napon: 90 to 264 V AC; Ulazna frekvencija: 47 to 63 Hz; Max ulazna struja: 1A at 240 V AC; Max Inrush current: 60 A at 230 V AC; Dimenzije: 172 x 257 x 43 mm.	366,46	305,38
DPS-800		R1462	Rack mount Nosač za dva redudantna napajanja.	124,45	103,71
INDUSTRIJSKI SWITCHEVI					
DIS-100G-5SW		R1463	Industrial Gigabit Unmanaged Switch with SFP slot; 4 x 100/1000Base-T ports, 1 x 100/1000BaseSFP slots; Unmanaged plug-and-play simplicity; Withstands extreme temperatures; Certified for vibration, shock, free-fall, NEMA-TS2 Section 2, EMC.	262,12	218,43
DIS-100G-5PSW		R1464	Industrial Gigabit PoE Unmanaged Switch with SFP slot; 4 x 100/1000Base-T ports PoE, 1 x 100/1000BaseSFP slots; PoE budget: 120W; Unmanaged plug-and-play simplicity; Withstands extreme temperatures; Certified for vibration, shock, free-fall, NEMA-TS2 Section 2, EMC.	463,08	385,90
RUTERI					
DWM-312		R1466	4G LTE M2M Router; Speeds up to 150 Mbps; Fast Ethernet; Dual-SIM slot; Zinc-plated steel case for durability; Withstands extreme temperatures and humidity.	343,56	286,30
ACCESS POINT					
DAP-2020		R1467	Wireless N Access Point; Mrežni standardi: 802.11 b/g/n do 300Mbps; Interfejsi 1xLAN, QoS; 2x5dBi antene, na 2,4GHz; Režimi rada: Access point, Bridge, Repeater; Enkripcije: 64/128-bit WEP data encryption; WPA-PSK, WPA2-PSK, WPA-EAP, WPA2-EAP, TKIP, AES; Dimenzije: 147,5 x 113 x 31,5 mm; Temperatura ambijenta rada: 0 to 40 °C.	35,42	29,52
DAP-2662		R1470	Wireless AC1200 Wave 2 Dual-Band PoE Access Point; 2x2 MU-MIMO; Režimi-Access Point, Wireless Client, WDS with AP; Mrežni standardi: IEEE802.11 a/b/g/n/ac Wave 2 wireless; Interfejsi 1x Gigabit LAN PoE; 4 internal dual-band 3 dBi omni antennas; Two internal 3 dBi for 2.4 GHz; Two internal 4 dBi for 5 GHz; 2.4 GHz band: 2.4 to 2.4835 GHz; 5 GHz band: 5.15 to 5.35 GHz; 5.47 to 5.85 GHz; 2.4 GHz Up to 300 Mbps; 5 GHz Up to 867 Mbps; Dimenzije: 170 x 170 x 28 mm; Temperatura ambijenta rada: 0 to 40 °C.	205,00	170,83
DBA-1210P		R1471	Nuclias Cloud-Managed AC1300 Wave 2 Access Point; Mrežni standardi: IEEE 802.11 a/b/g/n/ac Wave 2 wireless; Antena • Built-in 2 x 2 MU-MIMO antenna; 1 x 10/100/1000 Mbps Ethernet PoE port; 2.4 GHz Up to 450 Mbps; 5 GHz Up to 867 Mbps; Dimenzije: 170 x 170 x 28 mm; Temperatura ambijenta rada: 0 to 40 °C.	154,98	129,15
DNH-100		R1472	Nuclias Connect Hub DNH-100; Upravljanje do 100 AP istovremeno ili pojedinačno bez potrebe za dodatnim serverom; Upravljanje softverom Nuclias Connect; Upravljanje VLAN-ova za unapređeno upravljanje mrežom i podešavanjem SSID-a za bolju kontrolu; 1000Base-T Ethernet Port, USB 3.0 Port, Micro SD Slot; Izveštavanje o saobraćaju i analitika; Daljinsko podešavanje; AP monitoring; Managed AP, Rogue AP Authentication fail AP, Standalone AP; Podrška za interfejs komandne linije (CLI); Podrška za NAT Passthrough koja omogućava upravljanje s više mesta.	144,00	120,00
DAP-2360		R1473	AirPremier N PoE Access Point sa Plenum-rated kućištem; 802.11n 2.4GHz Single Band; Podržava 802.3af PoE / Gigabit Ethernet port; Podržava AP/WDS/WDS sa AP/AP Client mode; Multiple SSID/VLAN; Do 26dbm High Power radio antene; Podržava AP Manager II/ AP Array; D-View /SNMP /Web /Telnet /SSH /SSL; Dimenzije: 166mm x 188mm x 37mm.	60,00	50,00
WIFI I LAN EXTENDERI					
DHP-P601AV/E		R1474	DHP-P601AV/E kit; Adapter za prenos podataka preko strujne mreže; Maksimalna brzina 1000Mbps; Idealno za prostore gde je potrebno povezati udaljene tačke, između spratova i slično; Bitna napomena adapteri rade samo ako su povezani u okviru strujne mreže koje pokriva jedno brojilo.	67,80	56,50
SMART HOME					
PAMETNA UTICNICA DSP-W115/E		R1478	220V Wifi Smart Uticnica; Upoznajte D-Link Wifi pametnu uticnicu; Plug & Play povezivanje na kućnu Wifi Mrežu; Upali / Ugasi preko mobilnog telefona; Napravite dnevni ili nedeljni raspored paljenja i gašenja u određenom vremenskom periodu; Sprečite pregrevanje uređaja; Radi preko Google Home, Amazon Echo i IFTTT protokola.	34,96	29,13
PROFESIONALNA WI-FI OPREMA					

MODEL		ŠIFRA	OPIS	Cena sa PDV	CENA
DWL-3600AP		R1481	Unified Wireless N300 PoE AP ; Wi-Fi Interface: 802.11b/g/n, 802.3u/af; Lan Interface: 10/100/1000 Gigabit Ethernet; Antena: 2XMIMO sa 4 unutr. antene 4,7dBi; Napajanje: preko PoE ili strujnog adaptera; SSID: do 16 SSID, Station Isolation; Stand Alone Mode i Managed mode; Upravljiv sa D-Link Wireless Kontrolerima; Do 40 istovremeno konektovanih korisnika; Dimenzije: 203 x 203 x 48 mm.	206,72	172,27
DWL-6610AP		R1482	Unified Wireless AC dual band AP ; Wi-Fi interface: 802.11b/g/n 2.4 GHz wireless; 802.11ac/a/n 5 GHz wireless; Interface: 10/100/1000BASE-T LAN (PoE) port; IEEE 802.3af Power over Ethernet (PoE); Interne omni antene; 4 dBi za 5 GHz; 4 dBi za 2.4 GHz; 32 SSIDs; 802.1Q VLAN; Dimenzije: 205 x 39 mm	227,24	189,37
DWL-6700AP		R1483	Wireless Dual-Band Outdoor Unified Access Point ; Brzina protoka po segmentima: 802.11n: 6.5 Mbps-300 Mbps; 802.11a/g: 54, 48, 36, 24, 12, 9, 6 Mbps; 802.11b: 11, 5.5, 2, 1 Mbps; Portovi: 2x LAN; Interne 4 antene jačine: 8dBi (za 5GHz); 3dBi (za 2.4GHz); Dual Band (2.4 GHz & 5 GHz); Dimenzije: 280 x 115 x 50 mm.	277,13	230,94
DAP-3662		R1486	Wireless AC1200 Concurrent Dual-Band Outdoor ; IEEE 802.11ac wireless; Do 1200 Mbps; 2XGigabit LAN ports; Standard: IEEE 802.11a/b/g/n/ac1; IEEE 802.3u/ab/af; Frekvencije: 2.4 GHz band; 2.4 GHz to 2.4835 GHz; 5 GHz: 5.15 do 5.35 GHz, 5.47 do 5.85 GHz2; IP68 Vodootporno kućište; Vodootporno za temperature između -30 do 60°C; Gore-Tex® Technology omogućava da ne dolazi do kondenzacije unutar uređaja; 802.3af PoE; Dimenzije: 277 x 240 x 50 mm.	283,20	236,00
DAP-3320		R1487	Wireless N PoE Outdoor Access Point ; 10dBi Sektor antena 2.4GHz 802.11n / b / g; Dimenzije: 48 x 96 x 165 mm; Wireless N PoE: 10dBi Sektor antena 2.4GHz 802.11n / b / g; Interfejs: 802.11n/g/b wireless, Reset Button 10/100BaseT PoE Ethernet Port, Operativni Modovi: AP, WDS, WDS with AP, Wireless Client; Dimenzije: 105.43 x 228.6 x 35.86 mm.	80,40	67,00
OPTIČKI SFP MODULI					
DEM-310GT		****	GBIC Module for 1000BaseLX (LC Duplex) ; 1000Base-LX port (IEEE 802.3z standard); Duplex LC connector; Full duplex operation; 802.3x flow control support; Fibre type: 9um single-mode fibre, up to 10 km; Wavelength: 1310 nm; Power support: 3.3 V; Hot pluggable; MSA Compliant; RoHS Compliant.	73,93	61,61
DEM-431XT		****	SFP+ 10GBASE-SR Multi-Mode Fibre Transceiver (300m) ; Standard Compliance: IEEE-802.3ae, 10GBASE-SR; Transceiver Type - SFP+; Fibre Channel FC-Pi Standard -1200-Mx-SN-I; Fiber Media Support - Multi-Mode; Distance Capacity: 62.5 µm, 160 MHz-km: 26 m; 62.5 µm, OM1 200 MHz-km: 33 m; 50 µm, 400 MHz-km: 66 m; 50 µm, OM2 500 MHz-km: 82 m; 50 µm, OM3 2000 MHz-km: 300 m; Speed - 10 Gbps; Single/Bi Direction - Single-direction; Wavelength - 850 nm; Power support: 3.3 V; Hot pluggable; MSA Compliant; RoHS Compliant.	293,84	244,87
DEM-432XT		****	10GBASE-LR SFP+ Transceiver (10 Km) ; Standard Compliance: IEEE-802.3ae; 10GBASE-LRTransceiver Type -SFP+; Fibre Channel FC-Pi Standard -1200-SM-LL-L; Fiber Media Support: Single-Mode; Distance Capacity: 10 km; Brzina - 10 Gbps; Konektor- Duplex LC konektor; Single/Bi Direction - Single-direction; Wavelength - 1310 nm; Single-mode 9/125 um fiber; Power support: 3.3 V; Hot pluggable; MSA Compliant; RoHS Compliant.	554,03	461,69