

CENOVNIK D-LINK MREŽNE OPREME

Važi od 03. Marta 2021.

MODEL	ŠIFRA	OPIS	Cena sa PDV	CENA
NEUPRAVLJIVI (Unmanaged) SWITCHEVI				
DES-1024D	R1388	24 Portova Megabitni Switch; 24x 100 Mbps Ports; Standardi: IEEE 802.1p, IEEE 802.3, IEEE 802.3u, IEEE 802.3x; Dimenzije: 280 x 125.8 x 44 mm.	53,72	44,77
DGS-1016D	R0642	16 portova Gigabitni SOHO switch; 16x 10/100/1000 Mbps Gigabit ports; Switching Fabric: 32 Gbps; IEEE 802.3x Flow Control; Podržava IEEE 802.1p QoS; Plug-and-play instalacija; Dimenzije: 280 x 180 x 44 mm.	92,54	77,12
NEUPRAVLJIVI (Unmanaged) POE SWITCHEVI				
DES-1005P	R0652	5 Porta Megabitni PoE switch; 5x 10/100 Mbps Fast Ethernet ports; 1x PoE port; Standardi: IEEE 802.1p, IEEE 802.3, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x; Switching Capacity: 1 Gbps; PoE Power Budget Max. 15.4 W; Dimenzije: 140 x 85 x 28 mm; Desktop	51,76	43,13
DGS-1008P	R1389	8 Porta Gigabitni PoE switch; 8x 10/100/1000 Mbps Gigabit ports; 4x PoE ports; Standardi: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3u, IEEE 802.3x; Switching Capacity: 16 Gbps; PoE Power Budget Max. 52 W; Dimenzije: 190 x 120 x 38 mm; Desktop.	88,49	73,74
DES-1018P	R1390	16 Porta Megabitni PoE Switch; 2x Combo 1000Base-T/SFP ports; 16x PoE ports; PoE Power Budget Max. 246W; Dimenzije: 280 x 210 x 44 mm; Desktop / Rackmount.	328,58	273,82
UPRAVLJIVI (Managed) PoE SWITCHEVI				
DGS-3120-24SC-SI	R1458	24 Gigabit xStack L2+ Managed Gigabit Switches; 16 SFP Ports; 8 Combo 10/100/1000Base-T/SFP Ports; Switching Capacity: 88 Gbps; SD card slot; Dimenzije: 440 x 210 x 44 mm; Desktop / Rackmount.	869,94	724,95
DPS-500A	R1461	Redudantno napajanje; Izlazna snaga: 140 W; Ulazni Napon: 90 to 264 V AC; Ulazna frekvencija: 47 to 63 Hz; Max ulazna struja: 1A at 240 V AC; Max Inrush current: 60 A at 230 V AC; Dimenzije: 172 x 257 x 43 mm.	366,46	305,38
DPS-800	R1462	Rack mount Nosač za dva redudantna napajanja.	124,45	103,71
INDUSTRIJSKI SWITCHEVI				
DIS-100G-5SW	R1463	Industrial Gigabit Unmanaged Switch with SFP slot; 4 x 100/1000Base-T ports, 1 x 100/1000BaseSFP slots; Unmanaged plug-and-play simplicity; Withstands extreme temperatures; Certified for vibration, shock, free-fall, NEMA-12 Section 2, EMC.	262,12	218,43
DIS-100G-5PSW	R1464	Industrial Gigabit PoE Unmanaged Switch with SFP slot; 4 x 100/1000Base-T ports PoE, 1 x 100/1000BaseSFP slots; PoE budget: 120W; Unmanaged plug-and-play simplicity; Withstands extreme temperatures; Certified for vibration, shock, free-fall, NEMA-12 Section 2, EMC.	463,08	385,90
RUTERI				
DWM-312	R1466	4G LTE M2M Router; Speeds up to 150 Mbps; Fast Ethernet; Dual-SIM slot; Zinc-plated steel case for durability; Withstands extreme temperatures and humidity.	343,56	286,30
ACCESS POINT				
DAP-2020	R1467	Wireless N Access Point; Mrežni standardi: 802.11 b/g/n do 300Mbps; Interfejsi 1xLAN, QoS; 2x5dBi antene, na 2.4Ghz; Režimi rada: Access point, Bridge, Repeater; Enkripcije: 64/128-bit WEP data encryption; WPA-PSK, WPA2-PSK, WPA-EAP, WPA2-EAP, TKIP, AES; Dimenzije: 147.5 x 113 x 31.5 mm; Temperatura ambijenta rada: 0 to 40 °C.	35,42	29,52

MODEL	ŠIFRA	OPIS	Cena sa PDV	CENA
DAP-2662	R1470	Wireless AC1200 Wave 2 Dual-Band PoE Access Point; 2x2 MU-MIMO; Režimi-Access Point, Wireless Client, WDS, WDS with AP; Mrežni standardi: IEEE802.11a/b/g/n/ac Wave 2 wireless; Interfejsi 1x Gigabit LAN PoE; 4 internal dual-band 3 dBi omni antennas: Two internal 3 dBi for 2.4 GHz; Wave Two internal 4 dBi for 5 GHz; 2.4 GHz band: 2.4 to 2.4835 GHz; 5 GHz band: 5.15 to 5.35 GHz, 5.47 to 5.85 GHz; 2.4 GHz Up to 300 Mbps; 5 GHz Up to 867 Mbps; Dimenzije: 170 x 170 x 28 mm; Temperatura ambijenta rada: 0 to 40 °C.	205,00	170,83
DBA-1210P	R1471	Nuclias Cloud-Managed AC1300 Wave 2 Access Point; Mrežni standardi: IEEE 802.11a/b/g/n/ac Wave 2 wireless; Antena - Built-in 2 x 2 MU-MIMO antenna: 1 x 10/100/1000 Mbps Ethernet PoE port; 2.4 GHz Up to 450 Mbps; 5 GHz Up to 867 Mbps; Dimenzije: 170 x 170 x 28 mm; Temperatura ambijenta rada: 0 to 40 °C.	154,98	129,15
DNH-100	R1472	Nuclias Connect Hub DNH-100; Upravljanje do 100 AP istovremeno ili pojedinačno bez potrebe za dodatnim serverom; Upravljanje softverom Nuclias Connect; Upravljače više VLAN-ova za unapređeno upravljanje mrežom i podešavanjem SSID-a za bolju kontrolu; 1000Base-T Ethernet Port, USB 3.0 Port, Micro SD Slot; Izveštavanje o saobraćaju i analitika; Daljinsko podešavanje; AP monitoring; Managed AP, Rogue AP Authentication fail AP, Standalone AP; Podrška za interfejs komandne linije (CLI); Podrška za NAT Passthrough koja omogućava upravljanje s više mesta.	144,00	120,00
DAP-2360	R1473	Wireless N300 Single Band Gigabit; AirPremier N PoE Access Point sa Plenum-rated kućištem; 802.11n 2.4GHz Single Band; Podrška 802.3af PoE / Gigabit Ethernet port; Podrška AP/WDS/WDS sa AP/AP Client mode; Multiple SSID/VLAN; Do 26dbm High Power radio antene; Podrška AP Manager II/ AP Array; D-View /SNMP /Web /Telnet /SSH /SSL; Dimenzije: 166mm x 188mm x 37mm.	60,00	50,00
SMART HOME				
PAMETNA UTICNICA DSP-W115/E	R1478	220V Wifi Smart Uticnica; Upoznajte D-Link Wifi pametnu uticnicu; Plug & Play povezivanje na kućnu Wifi Mrežu; Upali / Ugasi preko mobilnog telefona; Napravite dnevni ili nedeljni raspored paljenja i gašenja u određenom vremenskom periodu; Sprečite pregrevanje uređaja; Radi preko Google Home, Amazon Echo i IFTT protokola.	34,96	29,13
PROFESIONALNA WI-FI OPREMA				
DWL-3600AP	R1481	Unified Wireless N300 PoE AP; Wi-Fi Interface: 802.11b/g/n, 802.3u/af; Lan Interface: 10/100/1000 Gigabit Ethernet; Antena: 2XMIMO sa 4 unutr. antene 4,7dBi; Napajanje: preko PoE ili strujnog adaptera; SSID: do 16 SSID, Station Isolation; Stand Alone Mode i Managed mode; Upravlja sa D-Link Wireless Kontrolerima; Do 40 istovremeno konektovanih korisnika; Dimenzije: 203 x 203 x 48 mm.	206,72	172,27
DWL-6610AP	R1482	Unified Wireless AC dual band AP; Wi-Fi interface: 802.11b/g/n 2.4 GHz wireless; 802.11ac/a/n 5 GHz wireless; Interface: 10/100/1000BASE-T LAN (PoE) port; IEEE 802.3af Power over Ethernet (PoE); Interne omni antene; 4 dBi za 5 GHz, 4 dBi za 2.4 GHz; 32 SSIDs; 802.1Q VLAN; Dimenzije: 205 x 39 mm	227,24	189,37
DAP-3662	R1486	Wireless AC1200 Concurrent Dual-Band Outdoor; IEEE 802.11ac wireless; Do 1200 Mbps; 2XGigabit LAN ports; Standardi: IEEE 802.11a/b/g/n/ac1; IEEE 802.3u/ab/af; Frekvencije: 2.4 GHz band: 2.4 GHz to 2.4835 GHz; 5 GHz: 5.15 to 5.35 GHz, 5.47 to 5.85 GHz; IP68 Vodootporno kućište; Vodootpomo za temperature između -30 do 60°C; Gore-Tex® Technology omogućava da ne dolazi do kondenzacije unutar uređaja; 802.3af PoE; Dimenzije: 277 x 240 x 50 mm.	283,20	236,00
DAP-3320	R1487	Wireless N PoE Outdoor Access Point; 10dBi Sektor antena 2,4GHz 802.11n / b / g; Dimenzije: 48 x 96 x 165 mm; Wireless N PoE; 10dBi Sektor antena 2,4GHz 802.11n / b / g; Interfejsi: 802.11n/g/b wireless, Reset Button 10/100BaseT PoE Ethernet Port, Operativni Modovi: AP, WDS, WDS with AP, Wireless Client; Dimenzije: 105.43 x 228.6 x 35.86 mm.	80,40	67,00
OPTIČKI SFP MODULI				
DEM-310GT	****	GBIC Module for 1000BaseLX (LC Duplex); 1000Base-LX port (IEEE 802.3z standard); Duplex LC connector; Full duplex operation; 802.3x flow control support; Fibre type: 9um single-mode fibre, up to 10 km; Wavelength: 1310 nm; Power support: 3.3 V; Hot pluggable; MSA Compliant; RoHS Compliant.	73,93	61,61
DEM-431XT	****	SFP+ 10GBASE-SR Multi-Mode Fibre Transceiver (300m); Standard Compliance: IEEE-802.3ae, 10GBASE-SR; Transceiver Type - SFP+; Fibre Channel FC-PI Standard -1200-Mx-SN-I; Fiber Media Support - Multi-Mode; Distance Capacity: 62.5 µm, 160 MHz-km; 26 m; 62.5 µm, OM1 200 MHz-km; 33 m; 50 µm, 400 MHz-km; 66 m; 50 µm, OM2 500 MHz-km; 82 m; 50 µm, OM3 2000 MHz-km; 300 m; Speed - 10 Gbps; Single/Bi Direction - Single-direction; Wavelength - 850 nm; Power support: 3.3 V; Hot pluggable; MSA Compliant; RoHS Compliant.	293,84	244,87
DEM-432XT	****	10GBASE-LR SFP+ Transceiver (10 Km); Standard Compliance: IEEE-802.3ae; 10GBASE-LR Transceiver Type -SFP+; Fibre Channel FC-PI Standard -1200-SM-LL-L; Fiber Media Support; Single-Mode; Distance Capacity: 10 km; Brzina - 10 Gbps; Konektor- Duplex LC konektor; Single/Bi Direction - Single-direction; Wavelength - 1310 nm; Single-mode 9/125 um fiber; Power support: 3.3 V; Hot pluggable; MSA Compliant; RoHS Compliant.	554,03	461,69